


Poz cija	Daudz.	Apraksts
	1	<p>SOLOLIFT2 C-3</p>  <p>Uzman bu! Izstr d juma att ls var atš irties no faktisk izstr d juma izskata.</p> <p>Izstr d juma Nr.: 97775317</p> <p>Sololift2 C-3 is a small, compact automatic lifting station suitable for pumping of greywater (w/o faeces) off places in private dwellings where wastewater cannot be led directly to the sewer by means of a natural downward slope.</p> <p>Sololift2 C-3 is typically used for:</p> <ul style="list-style-type: none"> • cabinet showers, washbasins, bath tubs, washing machines (max. 90°C) and dishwashers in basements below sewer level or in connection with the renovation or modernisation of existing buildings, where the location may be remote from the main soil pipe so that a natural slope cannot be established. <p>Sololift2 C-3 is suitable for installation under a washbasin or particularly for confined space conditions in prewall constructions and built-in cabinets. Extremely low switching levels for lowest construction heights, advantageously in case of connection of a shower receptor.</p> <p>The compact lifting station is equipped with</p> <ul style="list-style-type: none"> - Cable with or without plug (see technical data) - Horizontal or vertical fastening possibility of discharge hose connector with several adaptors for pipes with Ø22-40mm - Integrated non return valve - Dry and high performance motor unit incl. thermal protection, level switch and controller - Flexible connectors for inlet (adjustable in height) of pipes Ø36 or 40 - Manual anti clogging function and separate drain connection for service - Venting valve with overflow protection - Uplift fixation clips <p>Design according to EN12050-2 and production inspection by external institute with unique features focused on quick installation, long lasting operation and easy clean service.</p> <p>Note: The discharge adaptor can be mounted vertical or horizontal. Vertical installation increase the flow (s. databooklet and curves)</p> <p>Š idrums: S kn jamais š idrums: Jebkurš tona š idrums Š idruma maksim l temperat ra: 75(90) °C Bl vums: 998.2 kg/m³</p> <p>Technical: Apstiprin jumi pases datu pl ksn t : CE,TR,LGA,VDEEMV,VDE L knes pielaide: ISO9906:2012 3B</p> <p>Materi li: Tvertne: PLASTIC</p>

Pozīcija	Daudz.	Apraksts
		Uzstādīšana: Skaitļi ieejas kanāliem: 32/36/40, 36/40/50 Skaitļi izejas kanāliem: 22/25/28/32/36/40 Pievaduskaits: 3X0,75MM2 Elektriskie dati: Ieejas jauda - P1: 640 W Tīkla frekvence: 50 Hz Nominālais spriegums: 1 x 220-240 V Nominālais strāvas: 3.1 A Cos phi - jaudas koeficients: 0,9 Nominālais griezumums: 2800 rpm Korpusa klase (IEC 34-5): IP44 Izolācijas klase (IEC 85): F Kabeļa garums: 1.2 m Kabeļa tips: H05VV-F Kabeļa uzgādes tips: SCHUKO Citi: Neto svars: 7.6 kg Bruto svars: 9.3 kg

97775317 SOLOLIFT2 C-3 50 Hz

